

# KP1250A-J

## PHASE CONTROL THYRISTOR



### Features

Center amplifying gate  
Metal case with ceramic insulator  
Low on-state and switching losses

### Application

Large power converter  
DC and AC switches  
Active & Passive inverter

$I_{T(AV)}$	1250 A
$V_{DRM}/V_{RRM}$	3100~4200 V
$I_{TSM}$	16KA
$I^2T$	1280 KA <sup>2</sup> S

Symb.		parameter	Test Conditions	$T_{J(°C)}$	Value	Unit
Current Ratings	$I_{T(AV)}$	Average on-state current	180° half sine wave 50Hz Double side cooled $T_{hs}=70°C$	125	1250	A
	$I_{T(AV)}$	Average on-state current	180° half sine wave 50Hz Double side cooled $T_{hs}=55°C$	125	1611	A
	$I_{TSM}$	Surge on-state current	10ms half sine wave $V_R=0.6V_{RRM}$	125	16	KA
	$I^2t$	$I^2T$ for fusing coordination		125	1280	KA <sup>2</sup> S
Characteristics	$V_{DRM}$ $V_{RRM}$	Repetitive peak off-state voltage Repetitive peak reverse voltage	$V_{DRM} \& V_{RRM} t_p=10ms$ $V_{DSM} \& V_{RSM}=V_{DRM} \& V_{RRM}+100V$	125	3100-4200	V
	$I_{DRM}$ $I_{RRM}$	Repetitive peak current	$V_{DM}=V_{DRM}$ $V_{RM}=V_{RRM}$	125	Max.120	mA
	$V_{TO}$	Threshold voltage		125	Max.1.17	V
	$V_{TM}$	Threshold voltage	$I_{TM}=3000A, F=32KN$	25	Max.2.80	V
	$r_T$	On-state slop resistance		125	Max.0.35	mΩ
	$I_H$	Holding current	$V_A=12V, I_A=1A$	25	20-300	mA
Dynamic Parameters	dv/dt	Critical rate of rise of off-state voltage	$V_{DM}=67\%V_{DRM}$	125	Max.500	V/μs
	di/dt	Critical rate of rise of on-state current	$V_{DM}=67\%V_{DRM}$ to 600A, Gate pulse $t_r \leq 0.5\mu s$ $I_{GM}=1.5A$	125	Max.200	A/μs
	$t_{rr}$	Reverse recovery time	$I_{TM}=500A, t_p=1000\mu s, V_R=50V$	125	20	μs
	$Q_{rr}$	Reverse Recovery charge	$di/dt=-20A/\mu s$	125	1700	μc
Gate Parameters	$I_{GT}$	Gate trigger current	$V_A=12V, I_A=1A$	25	40-300	mA
	$V_{GT}$	Gate trigger voltage		25	0.8-3.0	V
	$V_{GD}$	Non-trigger gate voltage	$V_{DM}=67\%V_{DRM}$	125	Min.0.3	V

## Thermal & Mechanical Data

Symb.	parameter	Test Conditions	$T_{J(c)}$	Value	Unit
$R_{th(j-h)}$	Thermal resistance Junction to heat sink	At 180° sine wave, double side cooled Clamping force 32KN		Max.0.017	°C/W
$F_m$	Mounting force			27-34	KN
$T_{stg}$	Stored temperature			-40-140	°C
$W_t$	Weight			850	g

## Dimensions:

C23





